

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):


- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Drilled Aug 1994


Actual







EXCELSIOR 6 - E. KALKASKA 1
GAS STORAGE FIELD
PLAN VIEW COMPOSITE PROJECTION

PROPOSED

HORIZONTAL SCALE 1" = 600 FT.



USED By Manner Eng.
 Bob Knolly & Petroleum
 Tech Transfer
 Council



Daily Report -- GENERAL CHEMICAL CANADA LTD.

Well Name: BRINE WELL P-7 TO P-4 #2

Field: ANDERDON TWP.

Log: BRADCO RIG #2

Test Csg. Pt: 1050'

Size: 8 5/8"

Log. Rep: KATHY McCONNELL

Well Pusher: SAM STEVENSON

Phone:

Date: 07-23-1998

Report No: 30

Job No:

Rept. Ending: 6:00A.M. 07-24

End Depth: 1747'

Start Depth: 1150'

Daily Cost: \$8,000.00

Total Cost: \$30,400.00

Fax:

Job Parameters:

Plane of Proposal: S88.5W

Surface Location N/S: 0.00

E/W: 0.00

Bottom Hole N/S: 4.65

E/W: 600.00

Log. Corr. True: 0.00

Grid: 0.00

Well Elevation: 10.00

Time and Activity Breakdown:

10:00 A.M. P.U. MOTOR #350001 G.L. SET ON 2.129, SURFACE TEST & T/IN.

10:30 A.M. R.U. W.C..

11:30 A.M. DRLG. W/116 STKS. 850 PSI., 800 TO 1,000 PSI. HYD. TQ.

12:00 Midnight 07-24-98

1:00 A.M. HIT CAVERN @ 1747' MD, 1144' TVD, 642' V.S., SHOULD HAVE BEEN 550' V.S.??

12 HRS. DRLG., 597', AVG. 50' PER HR.

1:30 A.M. PULL BACK 3 JTS. & GOING TO CIRC. TILL NOON W/ F.W..

NOTE the DATE!

Brine Well P-7, Anderdon 6-11-II

SECTION 4.0 - CASING AND CEMENTING SUMMARY

Surface Casing:

Csg. Size OD (mm)	Hole Size (mm)	Weight (kg/m)	Grade & Thread	Depth (mKB)	Cementing
298	381	69.94	K-55 ST&C	30.5 m	3.4 tonnes Class G cement + 2% CaCl ₂ - cmt to surface with 100% excess

Intermediate Casing:

Csg. Size OD (mm)	Hole Size (mm)	Weight (kg/m)	Grade & Thread	Depth (mKB)	Cementing
219	273	35.72	K-55 ST&C	307	Fill Cement - 10.5 tonnes Class G cement + 2% CaCl ₂ + 8% gel - cmt to surface with 100% excess Tail Cement - Class G cement + 2% CaCl ₂ - cmt volume will be calc to push fill cmt to surface

Horizontal Hole:

well bore intersect!

200 mm horizontal hole will be drilled in two directions to intersect with wells P-4 and P-10 (see plan view and cross-sectional view of horizontal portion of the well)

Production Casing:

Csg. Size OD (mm)	Hole Size (mm)	Weight (kg/m)	Grade & Thread	Depth (mKB)	Cementing
140	200	20.83	K-55 ST&C	370	hung in well head

GENERAL CHEMICAL CANADA LTD.
BRINE WELL #R-10 TO #R-5
ANDERDON TWP., ESSEX CO., MI

12:43 01-14-2000 Page 1

GREAT LAKES DIRECTIONAL DRILLING

Report of Survey

Minimum Curvature Method

MEASURED DEPTH	INCL.	DIRECTION	VERTICAL DEPTH	VERTICAL SECTION	RECTANGULAR COORDINATES	DLS Deg/100'
1130.00	0 54	N 9 0 E	1126.88	-1.30	9.18 N 1.54 E	
1161.00	24 24	N 73 0 W	1156.94	4.94	11.32 N 4.64 W	78.35
1187.00	58 48	N 73 0 W	1176.10	21.32	16.30 N 20.90 W	132.31
1203.00	76 18	N 88 0 W	1182.21	35.87	18.60 N 35.39 W	139.19
1213.00	82 0	S 83 0 W	1184.10	45.66	18.16 N 45.19 W	105.14
1225.00	90 6	S 73 0 W	1184.93	57.27	15.67 N 56.87 W	107.03
1235.00	94 30	S 71 54 W	1184.53	66.71	12.66 N 66.40 W	45.35
1245.00	96 0	S 72 24 W	1183.61	76.10	9.61 N 75.88 W	15.80
1256.00	93 24	S 75 48 W	1182.71	86.56	6.61 N 86.42 W	38.83
1266.00	92 54	S 78 54 W	1182.16	96.24	4.42 N 96.16 W	31.35
1276.00	93 54	S 83 6 W	1181.57	106.05	2.86 N 106.02 W	43.10
1286.00	94 36	S 86 18 W	1180.82	115.96	1.94 N 115.95 W	32.67
1296.00	93 12	N 90 0 W	1180.14	125.91	1.62 N 125.92 W	39.48
1306.00	90 30	N 87 48 W	1179.82	135.91	1.81 N 135.91 W	34.82
1315.00	87 36	N 85 12 W	1179.97	144.90	2.36 N 144.89 W	43.27
1325.00	86 0	N 83 24 W	1180.53	154.85	3.35 N 154.82 W	24.06
1335.00	84 30	N 80 36 W	1181.36	164.76	4.73 N 164.69 W	31.68
1346.00	85 18	N 79 18 W	1182.33	175.59	6.65 N 175.48 W	13.84
1356.00	86 42	N 77 36 W	1183.03	185.41	8.64 N 185.25 W	21.99
1366.00	87 30	N 75 42 W	1183.54	195.19	10.95 N 194.97 W	20.59
1376.00	87 54	N 77 12 W	1183.94	204.96	13.29 N 204.68 W	15.51
1386.00	88 24	N 78 54 W	1184.26	214.79	15.36 N 214.46 W	17.71
1396.00	88 48	N 81 0 W	1184.51	224.67	17.11 N 224.30 W	21.37
1405.00	89 12	N 83 0 W	1184.66	233.62	18.36 N 233.21 W	22.66
1415.00	90 0	N 84 42 W	1184.73	243.58	19.43 N 243.15 W	18.79
1425.00	90 30	N 86 0 W	1184.69	253.57	20.24 N 253.12 W	13.93
1435.00	90 24	N 85 42 W	1184.61	263.56	20.96 N 263.09 W	3.16
1445.00	90 6	N 87 30 W	1184.57	273.55	21.56 N 273.08 W	18.25
1455.00	89 42	N 89 0 W	1184.59	283.55	21.86 N 283.07 W	15.52
1464.00	89 24	N 90 0 W	1184.66	292.55	21.94 N 292.07 W	11.60
1474.00	89 6	S 88 54 W	1184.79	302.54	21.84 N 302.07 W	11.40
1484.00	89 0	S 87 30 W	1184.95	312.52	21.53 N 312.06 W	14.03
1494.00	88 42	S 86 24 W	1185.15	322.49	21.00 N 322.04 W	11.40
1504.00	88 18	S 85 48 W	1185.42	332.44	20.32 N 332.02 W	7.21
1514.00	89 18	S 86 30 W	1185.62	342.39	19.65 N 341.99 W	12.20

GENERAL CHEMICAL CANADA LTD.
BRINE WELL #R-10 TO #R-5
ANDERDON TWP., ESSEX CO., MI

12:45 01-14-2000 Page 2

MEASURED DEPTH	INCL.	DIRECTION	VERTICAL DEPTH	VERTICAL SECTION	RECTANGULAR COORDINATES	DLS Deg/100'
1524.00	90 0	S 86 54 W	1185.69	352.36	19.07 N 351.98 W	8.06
1534.00	90 30	S 87 18 W	1185.64	362.33	18.57 N 361.96 W	6.40
1544.00	90 24	S 87 30 W	1185.56	372.30	18.11 N 371.95 W	2.24
1553.00	89 42	S 88 12 W	1185.56	381.28	17.77 N 380.95 W	11.00
1563.00	87 54	S 88 18 W	1185.76	391.26	17.47 N 390.94 W	18.03
1573.00	87 24	S 87 42 W	1186.17	401.24	17.12 N 400.92 W	7.81
1583.00	89 6	S 88 48 W	1186.48	411.22	16.82 N 410.91 W	20.24
1593.00	89 24	S 87 48 W	1186.61	421.20	16.52 N 420.91 W	10.44
1603.00	88 24	S 87 12 W	1186.80	431.17	16.08 N 430.90 W	11.66
1614.00	88 24	S 87 30 W	1187.11	442.14	15.57 N 441.88 W	2.73
1624.00	89 42	S 88 48 W	1187.28	452.12	15.25 N 451.87 W	18.38
1634.00	91 6	N 89 0 W	1187.21	462.11	15.23 N 461.87 W	26.07
1643.00	89 12	N 89 12 W	1187.18	471.11	15.38 N 470.87 W	21.23
1653.00	88 48	N 89 54 W	1187.36	481.11	15.45 N 480.87 W	8.06
1663.00	90 24	S 89 12 W	1187.43	491.10	15.39 N 490.87 W	18.36
1673.00	90 42	S 88 48 W	1187.33	501.09	15.22 N 500.87 W	5.00
1683.00	90 0	S 88 30 W	1187.27	511.08	14.98 N 510.86 W	7.61
1693.00	89 54	S 89 12 W	1187.28	521.07	14.78 N 520.86 W	7.07
1703.00	90 12	S 89 18 W	1187.27	531.06	14.65 N 530.86 W	3.16
1713.00	90 30	N 88 24 W	1187.21	541.06	14.73 N 540.86 W	23.19
1723.00	90 6	N 88 6 W	1187.16	551.06	15.03 N 550.86 W	5.00
1733.00	88 48	N 89 0 W	1187.25	561.06	15.29 N 560.85 W	15.81
1743.00	88 0	S 89 54 W	1187.53	571.05	15.37 N 570.85 W	13.60
1753.00	88 6	N 89 30 W	1187.87	581.04	15.40 N 580.84 W	6.08
1762.00	89 24	S 89 48 W	1188.07	590.04	15.42 N 589.84 W	16.40
1772.00	90 24	S 89 54 W	1188.09	600.03	15.40 N 599.84 W	10.05
1782.00	91 6	N 88 54 W	1187.95	610.03	15.49 N 609.84 W	13.89
1792.00	91 36	N 87 18 W	1187.72	620.03	15.82 N 619.83 W	16.76
1802.00	92 0	N 86 12 W	1187.40	630.02	16.38 N 629.81 W	11.70
1812.00	91 0	N 86 24 W	1187.14	640.01	17.03 N 639.78 W	10.20
1822.00	90 36	N 86 48 W	1187.00	650.00	17.62 N 649.76 W	5.66
1832.00	90 36	N 87 12 W	1186.90	660.00	18.15 N 659.75 W	4.00
1842.00	91 30	N 86 6 W	1186.72	669.99	18.73 N 669.73 W	14.21
1853.00	90 54	N 87 18 W	1186.49	680.98	19.36 N 680.71 W	12.19
1863.00	90 18	N 87 24 W	1186.38	690.98	19.82 N 690.70 W	6.08
1873.00	88 36	N 87 42 W	1186.48	700.98	20.25 N 700.69 W	17.26
1882.00	89 12	N 89 6 W	1186.65	709.98	20.50 N 709.68 W	16.92
1892.00	90 36	N 89 24 W	1186.67	719.98	20.63 N 719.68 W	14.32
1902.00	91 54	N 89 18 W	1186.45	729.97	20.75 N 729.68 W	13.04
1915.00	92 12	N 89 6 W	1185.98	742.96	20.93 N 742.67 W	2.77

GENERAL CHEMICAL CANADA LTD.
BRINE WELL #R-10 TO #R-5
ANDERDON TWP., ESSEX CO., MI

12:47 01-14-2000 Page 3
RECTANGULAR DLS
COORDINATES Deg/100'

MEASURED DEPTH	INCL.	DIRECTION	VERTICAL DEPTH	VERTICAL SECTION	RECTANGULAR COORDINATES	DLS Deg/100'
1925.00	92 24	N 88 48 W	1185.58	752.95	21.11 N 752.66 W	3.60
1935.00	91 42	N 88 36 W	1185.22	762.95	21.34 N 762.65 W	7.28
1945.00	90 18	S 89 48 W	1185.05	772.94	21.44 N 772.65 W	21.26
1955.00	90 36	S 89 24 W	1184.97	782.94	21.37 N 782.65 W	5.00
1976.00	92 30	N 88 0 W	1184.40	803.93	21.63 N 803.64 W	15.33
1986.00	92 12	N 87 18 W	1183.99	813.92	22.04 N 813.62 W	7.61
1996.00	91 54	N 87 24 W	1183.64	823.91	22.50 N 823.60 W	3.16
2008.00	91 12	N 87 42 W	1183.31	835.90	23.01 N 835.59 W	6.35
2018.00	91 12	N 87 30 W	1183.10	845.90	23.43 N 845.57 W	2.00
2029.00	90 6	N 87 48 W	1182.98	856.90	23.88 N 856.56 W	10.36
2041.00	89 0	N 87 6 W	1183.07	868.89	24.42 N 868.55 W	10.86
2050.00	89 12	N 87 12 W	1183.21	877.89	24.87 N 877.54 W	2.48
2060.00	89 24	N 87 0 W	1183.33	887.89	25.37 N 887.53 W	2.83
2072.00	89 18	N 87 30 W	1183.47	899.88	25.95 N 899.51 W	4.25
2082.00	89 42	N 88 6 W	1183.56	909.88	26.33 N 909.50 W	7.21
2092.00	90 42	S 89 36 W	1183.52	919.88	26.46 N 919.50 W	25.08
2107.00	91 0	N 88 24 W	1183.30	934.88	26.62 N 934.50 W	13.48
2122.00	92 0	N 84 12 W	1182.91	949.86	27.59 N 949.46 W	28.77
2134.00	92 0	N 84 12 W	1182.49	961.81	28.80 N 961.39 W	0
2149.00	92 0	N 84 12 W	1181.96	976.76	30.31 N 976.30 W	0

Final location: 976.77 feet at N 88 13 W
Plane of Vertical Section: 271.52 degrees

GREAT LAKES DIRECTIONAL DRILLING

Report of Survey

Minimum Curvature Method

MEASURED DEPTH	INCL.	DIRECTION	VERTICAL DEPTH	VERTICAL SECTION	RECTANGULAR COORDINATES		DLS Deg/100'
1925.00	92.40	271.20	1185.58	752.93	21.11 N	752.66 W	
1935.00	91.70	275.00	1185.22	762.92	21.65 N	762.64 W	38.61
1946.00	92.00	277.50	1184.87	773.88	22.85 N	773.57 W	22.88
1956.00	91.40	279.30	1184.57	783.82	24.31 N	783.45 W	18.97
1966.00	90.40	279.30	1184.41	793.74	25.92 N	793.32 W	10.00
1976.00	89.20	278.80	1184.45	803.66	27.50 N	803.20 W	13.00
1986.00	87.90	277.40	1184.70	813.60	28.90 N	813.09 W	19.10
1997.00	87.50	274.80	1185.14	824.57	30.07 N	824.02 W	23.89
2009.00	88.90	274.70	1185.52	836.55	31.07 N	835.97 W	11.70
2019.00	89.20	274.00	1185.68	846.54	31.82 N	845.94 W	7.61
2029.00	89.60	275.70	1185.79	856.53	32.67 N	855.91 W	17.46
2041.00	89.80	275.60	1185.85	868.50	33.85 N	867.85 W	1.86
2051.00	90.30	273.30	1185.84	878.49	34.63 N	877.82 W	23.54
2061.00	91.30	274.00	1185.70	888.49	35.26 N	887.79 W	12.21
2072.00	91.20	273.00	1185.46	899.48	35.93 N	898.77 W	9.13
2082.00	90.70	271.70	1185.30	909.48	36.34 N	908.76 W	13.93
2092.00	89.10	269.20	1185.32	919.47	36.42 N	918.76 W	29.68
2123.00	92.20	270.10	1184.96	950.44	36.23 N	949.75 W	10.41
2133.00	93.10	271.00	1184.50	960.43	36.33 N	959.74 W	12.72
2164.00	93.00	271.00	1182.85	991.38	36.87 N	990.69 W	.32

Final location: 991.38 feet at 272.13 degrees
Plane of Vertical Section: 272.07 degrees

GENERAL CHEMICAL
BRINE WELL R-10 TO R-5
ANDERDON TWP., ESSEX CO., ONTARIO

12:37 01-14-2000 Page 1

GREAT LAKES DIRECTIONAL DRILLING

Report of Survey

Minimum Curvature Method

MEASURED DEPTH	INCL.	DIRECTION	VERTICAL DEPTH	VERTICAL SECTION	RECTANGULAR COORDINATES	DLS Deg/100'
1966.00	90 24	N 80 42 W	1184.41	793.74	25.92 N 793.32 W	
1997.00	87 30	N 85 36 W	1184.98	824.61	29.62 N 824.08 W	18.36
2009.00	89 36	N 84 18 W	1185.28	836.59	30.67 N 836.03 W	20.58
2092.00	89 6	S 89 12 W	1186.22	919.54	34.22 N 918.90 W	7.85
2123.00	92 18	N 90 0 W	1185.85	950.50	34.00 N 949.90 W	10.64


Final location: 950.50 feet at N 87 57 W
Plane of Vertical Section: 272.07 degrees

GENERAL CHEMICAL
AMHERSTBURG, ONT.

SONARWIRE, INC
Vertical Cross Section

BRINE WELL NO. R-5
R-5 Fr, Oct 29, 1999

*Note enlarged cavity for
intercept*



ANDERDON TWP., ESSEX CO., MI

